


integra Vivid



Touchscreen for Markoprint print systems

- 7" high resolution color display with capacitive touch display
- Compact, robust system for easy integration on the production line
- Displaying the print jobs and status of an X1JET system, integra PP 108 or integra PP RAZR
- Editing printer settings and changing print jobs directly on the display



Inspired by customer requirements

Inspired by customer requirements, the integra Vivid stands for modern touch operating technology with an innovative swipe user interface.

The 7" high-resolution HMI color display is used to visualize the print jobs and the status of X1JET and PP Class printing systems. At a glance, you can see whether the printing system is currently working, what the ink level of the cartridges is, and at what speed printing is taking place. Editing printer settings and changing print jobs is now easier and more innovative to do directly on the display.

With its IP52 protection class, it is protected in dusty production environments and against falling dripping water.

Performance data	
Supported print systems	XIJET systems, integra PP 108 and integra PP RAZR
Supported print technologies	HP, LX, MX, XR, PP
Max. number of print heads	1
Max. number of production lines	1
Weight system	1275 g
Weight holder	500 g
Display size	7" (17,8 cm)
Depth	27,3 mm
Width	200,6 mm
Height	132,2 mm (without holder and connections)
Text design	over idesign8+ Software
Parameter input	over idesign8+ Software as well as at the integra Vivid
User language	German, English
Protection class	IP52
Temperature range	5 to 40°C
Relative humidity, max.	10 to 90% (non-condensing)
Max. operating time	The device is designed for continuous operating

Technical changes reserved at any time

Any number of print images

The compact, robust system can be easily integrated on the production line thanks to its small space requirement. A holder allows it to be placed on the table or mounted on the wall.

The system starts automatically with the connected printing system. Print images can be selected, started and paused directly via the touch display. If the selected print image contains a variable field, the option to enter the variable text appears after the print selection.

The integra Vivid can be used to print any number of print images. The integra Vivid can also be removed during operation and used for other XIJET, integra PP 108 or integra PP RAZR systems (hot plugging).



Weber Marking Systems GmbH

Headquarter: Maarweg 33 • D-53619 Rheinbreitbach

Tel: +49 (0) 2224/7708-0 • Fax: +49 (0) 2224/7708-20

info@weber-marking.com • www.weber-marking.com